

Butterfly 3600

Indirect or Wallwash LED

120-277VAC | IP66

Project
Date



CCT	30K, 35K, 40K, 50K								
Length	16"						24"		
LED Output	L25	L50	L75	L90	L120	L150	L200	L270	L340
Wattage	25W	50W	75W	90W	120W	150W	200W	270W	340W
Lumens	3,500	7,000	10,500	12,600	16,800	21,100	28,000	37,800	47,600
Weight	12 lbs						16 lbs		

DESCRIPTION

The Butterfly is a powerful indirect LED wall or pendant mounting fixture which provides forward throw indirect lighting. The slim, clean architectural design with superior performance eliminates the discomfort of the glare associated with direct LED lighting. Designed for illuminating large volume spaces such as malls, sports halls and airports.



FEATURES

Construction	Durable Die-Cast Aluminum Housing. Stainless Steel Hardware. High impact protective lens.
Dimensions (WxLxH)	13"W x 16.75"L x 2.8"H / 13"W x 24.75"L x 5.125"H
Weight	16" - 12lbs / 24" - 16lbs
CCT	3000K, 3500K, 4000K, 5000K
Dimming	Non-dimming, 0-10V Dimming
Optics	Standard Forward Throw or Optional Wide Forward Throw Rotatable Lenses (Every 90°)
Mounting	Flush Mount, Extended Arm, Pendant Mount (Single, Double, Triple, Quad).
Finish	Epoxy Powder Coated Silver, White, Black, Bronze, Custom


PERFORMANCE

Electrical	120-277V AC / 277-480V AC Input line voltage
LED Wattage	25W, 50W, 75W, 90W, 120W, 150W, 200W, 270W, 340W
Environment	IP66 - Suitable for Wet Locations. Natatorium - Marine Grade Finish Operating Temperature - 40°F to 122°F
Warranty	5 yr / 50,000 hour limited warranty
CRI	80+
Certifications	UL Listed


LENGTHS (NOM.)



STANDARD FORWARD THROW



OPTIONAL WIDE FORWARD THROW



ORDERING GUIDE Make selections by filling out the top row or highlighting options.

3600								
SERIES	LENGTH	OUTPUT	CCT	VOLTAGE	CONTROL	MOUNTING	FINISH	ACCESSORY
3600	16 16" nom	L25 25W L50 50W L75 75W L90 90W L120 120W L150 150W	30 3000K 35 3500K 40 4000K 50 5000K	U 120-277V U2 277-480V	ND NON DIMMING D1 0-10V DIMMING	Ax* EXTENDED ARM BF FLUSH MOUNT PSx* PENDANT SINGLE X PDx* PENDANT DOUBLE X PTx* PENDANT TRIPLE X PQx* PENDANT QUAD X CU CUSTOM MOUNT <small>36" MAX EXTENDED ARM 120" MAX PENDANT</small>	SO SILVER WH WHITE BL BLACK BZ BRONZE CU CUSTOM	M MARINE GRADE FINISH 2 NATATORIUM E EMERGENCY DRIVER (remote location) W WIDE OPTIC N NONE
	24 24" nom	L200 200W L270 270W L340 340W						


Specifications sheets are subject to change without notification.

X=STEM LENGTH (IN INCHES)




PHOTOMETRICS


25 WATT - FORWARD THROW




25 WATT - WIDE FORWARD THROW




50 WATT - FORWARD THROW




50 WATT - WIDE FORWARD THROW




75 WATT - FORWARD THROW




75 WATT - WIDE FORWARD THROW




90 WATT - FORWARD THROW




90 WATT - WIDE FORWARD THROW



120 WATT - FORWARD THROW




120 WATT - WIDE FORWARD THROW




PHOTOMETRICS


150 WATT - FORWARD THROW




150 WATT - WIDE FORWARD THROW




200 WATT - FORWARD THROW




200 WATT - WIDE FORWARD THROW




270 WATT - FORWARD THROW




270 WATT - WIDE FORWARD THROW




340 WATT - FORWARD THROW



340 WATT - WIDE FORWARD THROW



ADJUSTABLE LENS ANGLE




Each lens can be rotated 90°. You can adjust angle according to your requirement.



DIMENSIONS

LENGTHS

16" FIXTURE





24" FIXTURE



MOUNTING OPTIONS



Ax Extended Arm

Available in 4"-36" lengths. Power cords are routed through arms, exiting close to the wall to connect to an adjacent j-box or other power outlet, providing a tidy installation.



BF Flush Mount

Standard mounting with back plate.





Specifications sheets are subject to change without notification.

Butterfly® 3600

MOUNTING OPTIONS AND ACCESSORIES

PS36, PD36 Single, Double Pendant Mount


Available for single and double fixtures. Standard 36" stems. Fixtures are designed to be mounted above 6' 4".



ACCESSORIES

W Wide Optic

Wide forward throw lens



ADD-ONS

Surge Protection



Part # 3650LEDSP10KU
(Surge Protection 10KV 120-277V)



Part # 3650LEDSP20KU
(Surge Protection 20KV 120-277V)



Part # 3650LEDSP20KU2
(Surge Protection 20KV 347-480V)

Dusk to Dawn Photocell




Part # 3650LEDPH
(Twist Lock Photocell & Receptacle 120-277V)

Specifications sheets are subject to change without notification.

Butterfly 3600


ELECTRICAL DETAILS

Non-Dimming | 3 Wire | 120-277V



BLACK	WHITE	GREEN
POWER +	NEUTRAL -	GROUND

0-10V Dimming | 5 Wire | 120-277V



BLACK	WHITE	GREEN	PURPLE	GREY
POWER +	NEUTRAL -	GROUND	DIM +	DIM -